Ares850

Slim Edge POS Terminal



Features

- 15" all-in-one panel PC with bezel-free touch display
- Power efficient Intel[®] 12th Gen (Alder Lake-P) Core[™] Processors
- Easy access M.2 SSD for installation and maintenance
- Optional VFD, 9.7" & 15" attached customer display
- Optional MSR, iButton, fingerprint, 2D scanner and RFID
- Support Type C USB 3.2 Gen1
- Trusted Platform Module 2.0 for data security
- Support NVMe 2.0

Model			Ares850
Display	Display Size		15" TFT LCD 🔊
	Resolution		1024 X 768
	Brightness/ Color		300 cd/m [*] , 16.2M colors
	Backlight		LED
Touch Panel	Туре		Projected capacitive touch
Processor	CPU/ Chipset		Intel® Core™ i5-1245UE Intel® Core™ i3-1215UE
Memory			X 2 SO-DIMM socket supports up to 32GB
Storage			X 1 (M.2 SSD M-Key supports 2242 & 2280) NVMe PCI-e Gen3 X 4
			X 1 (M.2 SSD M-Key Supports 2242 & 2280) only SATA
I/O Connectors	USB 2.0		X 5 (Rear X 4, Side X 1)
	USB 3.2 Gen1		X 3 (Rear)
	USB Type-C 3.2 Gen1		X 1
	WIFI		X 1 E-Key (Supports WiFi & Bluetooth)
	Powered COM		X 3 (RJ45 Powered COM 5V/ 12V selected by BIOS)
	Powered USB 2.0		X 1 Powered USB 24V (Retain adapter 150W)
	Cash Drawer Port		X 1 (24V RJ11 cash drawer port)
	Audio Port	Speaker	X 1 (2W)
		Line Out	X 1
	LAN		X 1 (RJ45 10/ 100/ 1000 Base-T)
	DC In		Lockable 3-pin DC input
Optional Peripherals			VFD/ 2 nd display 9.7" & 15"/ MSR/ iButton/ RFID/ Fingerprint/ 2D Scanner/ Printer Stand
Power Supply			90W/ Option 150W 19V lockable 3-pin power adapter
OS Support			Windows 10 IoT
Environment	Temperature	Operation	32 [°] to 95 [°] F (0 [°] to 35 [°] C)
		Storage	-4° to 140° F (-20° to 60° C)
	Relative Humidity		20% to 80% non-condensing
Dimension (W x H x D) mm			347 x 221 x 334 mm
Certifications			CE/ FCC/ LVD
Protection			IP64 on front bezel

Specifications are subject to change without notice.

clientron




www.clientron.com

Ares850

Slim Edge POS Terminal




15" solid aluminum die-casting rear cover with fanless design is powered by Intel[®] Celeron[®] Elkhart Lake J6412



Easy access M.2 SSD M-Key PCI-e Gen 3 x 4 NVME



PCI-E Gen3 x4 M.2 SSD with 4 times faster speed than SATA3



Trusted Platform Module for data security




Optional VFD/ 2nd display 9.7" & 15"/ MSR/ iButton/ RFID/ Fingerprint/ 2D Scanner




Support Type C USB 3.2 Gen1

Mechanical Layout / Drawing



I/O Interface



www.clientron.com