

VD1220

VFD Customer Display Features Stylish Design and Bezel-free Display with Wide Viewing Angle



Features

- Stylish design with bezel-free display
- Supports OPOS driver
- 20 columns x 2 lines customer display with wide viewing angle
- Compatible with 9 command modes including EPSON and Logic Control command
- Supports multi-language
- Adjustable height, swivel and tilt angles for display

Specification

Model	VD1220
Display Method	Vacuum Fluorescent Display
Number of Characters	40 (20 columns X 2 Lines)
Brightness	350~700 cd/m ²
Character Font	5 X 7 Dot Matrix
Character Type	95 alphanumeric, 32 international characters
Character Size (W x H)	6.7 X 3.7 mm
Dot Size (W x H)	0.5 X 0.7 mm
Height	118mm with stand-alone base
	418mm with base and 2 extension
Panel Dimension (W x H x D) / Color	72 X 184 X 40 mm / Black
Pole Dimension	Per support length : 150mm(by 2)
Base Dimension (W x H x D)	36.5 X 200 X 95mm
Tilt Angle	Max 45°
Swivel Angle	Max 336°
Weight	Approx. 1000 grams
Commands Mode	EPSON, AEDEX, UTC/S, UTC/E, ADM788, DSP800, CD5220, EMAX, LOGIC CONTROL
Language Support	US English, Standard European, French, Germany, UK, Danish I&II, Swedish, Italian, Spanish, Katakana, Norwegian, Portuguese, Slavonic, Russian, Latvian, Greek, Nordic, Croatia, Bosnia, Hungarian, Romanian, Czech, Bulgaria, Finnish, Turkish, Hebrew
Interface	RS232/USB
Connection (Baud Rate)	Direct connection 9600 or 19200 bps
Reliability (MTBF)	30,000 hours
Power (Consumption)	5V

Specifications subject to change without notice.

Mechanical Layout / Drawing

